

Bone Stock V8, Compact

GENERAL

1. NO Imps NO Suicides

NO Hearses

NO Ambulances

NO Trucks or Truck Frames

Any question on car choice, please ask.

2. This class is open to any FWD or RWD V8, V6 or 4 cylinder car (other than what's listed).

3. NO WELDING. Two wires or chains per door. Two wire hold downs for hood. Two wire hold downs for trunks. No additional material may be added.

4. Move battery to passenger side floor board or front seat area. No milk crates, no zip ties, no zip screws can be used. Metal Battery box, BOLTED to the floor.

5. Move gas tank. (Make sure its secure, no zip Screws)

6. FACTORY shifter or simple threaded rod (NO AFTERMARKET)

7. Stock street tires – no ags, no skids. Any ply DOT street tires only - DOT marking must be visible. Small weld in centers will be allowed. Sidewall flaps will be allowed.

8. No aftermarket parts with the exception of a transmission cooler (fan or ice) will be allowed and must be secured.

9. Stock pedals

10. Any OEM car bumper can be used. Must be bolted on with factory bolts and remain in original location with factory sized bolts and factory number of bolts. You may weld the front bumper on with 4" of weld total per frame rail. FRONT AND REAR bumper must have 9 wire or chain in two locations thru core support, (or) hood, (or) speaker deck, (or) roof only to hold them on. It may NOT go to the frame, DO NOT WELD. Chain cannot be larger than 5/16" and no more than 3 strands of 9 wire. Do not shorten frame.

11. No suspension modifications

12. No body creasing

13. No tucking

14. No added bumper shocks

15. Headers will be allowed

16. You can weld your rear center to make it posi

2023

17. Motor swaps allowed – weld the factory mounts in and that is it
 18. One chain per motor mount. Must be bolted to factory frame hole. Max of 18" long.
 19. No excessive mounts (max 8 inches of weld per mount)
 20. No added steel
 21. No cradles
 22. Factory trans mount and cross-member
 23. A 4-point cage will be allowed – for driver protection only! Anything in excess will be forced to cut or loaded at judge's discretion.
 24. Cage must be 5 inches from floor and firewall at any point.
 25. Simple tank protector allowed, off the back bar only must be 8 inches from any sheet metal, keep it tight to the tank, do NOT ABUSE THIS rule or we will take it away.
 26. DO NOT WELD...IF IT DID NOT COME OFF THE FACTORY FLOOR DO NOT DO IT.
- OEM bolt on Only!!